

METRO TILES – ALL COLOURS – 100 X 200 MM

Characteristics		ISO	Result
Manufacture Process		Single Firing	Dry Pressed Ceramic Wall Tile
THICKNESS		EN ISO 10545-2	7 mm
LENGTH, WIDTH, THICKNESS, SIDE STRAIGHTNESS, ORTOGONALITY AND FLATNESS		EN ISO 10545-2	Conform to the requisites applicable to each model as defined in the standard UNE-EN 14411 (ISO 13006) for group BIII
WATER ABSORPTION		EN ISO 10545-3	15.2%
FLEXURAL RESISTANCE		EN ISO 10545-4	> 23 N/mm ²
LINEAL THERMIC DILATATION		EN ISO 10545-8	< 7·10 ⁻⁶ /°C
THERMIC IMPACT RESISTANCE		EN ISO 10545-9	It stands the test
EXPANSION DUE TO MOISTURE		EN ISO 10545-10	< 0.6%
CRACKING RESISTANCE		EN ISO 10545-11	It stands the test
FROST RESISTANCE		EN ISO 10545-12	It stands the test
CHEMICAL RESISTANCE	SOFT & STRONG, BASES & ACIDS	EN ISO 10545-13	Type GLA GHA
	CLEANSING PRODUCTS & CHEMICAL PRODUCTS FOR SWIMMING POOLS		Type GA
STAIN RESISTANCE		EN ISO 15045-14	Type 5
SCRATCH RESISTANCE (MoHS)		UNE 671010 (EN 101)	2
RADIOACTIVE TEST			Apt for the construction