


RIB (ALL COLOURS) 100x200 / 150.2x170.2 / 75X300


Characteristics	Performance	Standard
REACTION TO FIRE	A1 _{FL} / A1	EN 1411:2016
RELEASE OF DANGEROUS SUBSTANCES		
CADMIUM	PND / NPD	
LEAD	PND / NPD	
BREAKING STRENGTH	> 1000 N	
SLIP RESISTANCE		
UN-ENV 12633:2003 ANEXO A	> 15	
BOND STRENGTH ADHESION		
CEMENTITIOUS ADHESIVE TYPE C1	> 0.5 N/mm ²	
DURABILITY FOR:		
INTERIOR APPLICATIONS	COMPLY	
TACTILE PROPERTIES	PND / NPD	
WATER ABSORPTION	E > 10%	
COLOUR VARIATION	V ₂ [*]	

For interior Walls


Degree of colour change:



Low
V1



Medium
V2



High
V3



Random
V4

- Low V1 THE LEAST AMOUNT OF SHADE AND TEXTURE VARIATION
- Medium V2 LIGHT TO MODERATE SHADE AND TEXTURE VARIATION WITHIN EACH CARTON.
- High V3 HIGH SHADE AND TEXTURE VARIATION WITHIN EACH CARTON
- Random V4 VERY HIGH SHADE AND TEXTURE VARIATION WITHIN EACH CARTON